

ALTEZZA INTERNA (m)	2.70	AREA TOTALE (m²)	14.74	RV	DATA	D	A
USO:	----	FOGLIO:	PIANTA E PROSPETTI	00	16.05.2025	G.C.	F.D.
DISEGNO N° QC21				01	.	.	.
				SCALA			1:50

Questo disegno è di proprietà di QCOON S.r.l. - Tutti i diritti sono riservati a norma di legge. E' vietato la copia e la riproduzione dei contenuti in qualsiasi forma.

Technical drawing of a refrigerator with five doors. The height is indicated as 3042. The drawing shows the front view with a top and bottom panel and five main doors. The bottom panel has two small rectangular cutouts. The refrigerator is shown sitting on a hatched base.

PIANTA

The floor plan shows a rectangular room with a total width of 6055 mm and a total depth of 2435 mm. The internal height is 2700 mm. The layout includes a central sink with a mirror above it, two toilets on the right side, and a shower area on the left. Dimensions for fixtures and clearances are provided: 2350 mm for the main open area, 1800 mm for the vanity area, and 1080 mm for the toilet stalls. Fixtures are labeled with '750 2060' and '500W'. A door is shown on the left wall, and a window is indicated on the right wall. A red arrow points to the door, and a blue arrow points to the window.

Technical drawing of a refrigerator unit, showing a side view. The unit is a dark-colored, five-door refrigerator. A vertical dimension line on the left indicates a height of 3042. The unit is shown sitting on a base, and the floor is indicated by a hatched pattern at the bottom.

Technical drawing of a two-door electrical cabinet (Schrank 3042). The cabinet is shown in a front view, featuring two doors with viewing windows. The drawing includes dimensions: a height of 1800 mm and a width of 600 mm. The cabinet is mounted on a base with four leveling feet. The doors have a dark grey finish, and the viewing windows are protected by blue diagonal lines. The top of the cabinet has two locking mechanisms. The drawing is labeled '3042' on the right side.

LEGENDA ELETTRICA	
	QUADRO ELETTRICO MONTATO A PARETE
	INGRESSO ELETTRICO SPINA/PRESA
	PLAFONIERA TONDA
	PLAFONIERA TONDA CON RIVELATORE DI PRESENZA
	INTERRUTTORE
	PRESA DI SERVIZIO TIPO SCHUKO IP40
	PRESA DI SERVIZIO TIPO SCHUKO IP55
	BOILER ELETTRICO 10LT
	ALIMENTAZIONE DIRETTA
	TERMOCONVETTORE 500W
	ESTRATTORE D100mm
IL PROGETTO E LA FORNITURA NON PREVEDONO LA PROTEZIONE CONTRO LE SOVRATENSIONI (RIF. NORME CEI 64-8 V5)	

LEGENDA SIMBOLOGIA IDRAULICA:	
	SCARICO A PARETE DN110
	INGRESSO ALIMENTAZIONE ACQUA A PARETE CON RACCORDO FILETTATO MASCHIO 1/2" ($p_{max} = 3atm$)
	PILETTE DI SCARICO A PAVIMENTO DN40